

Nomenclature Abbreviations

END CONNECTION

Gasketed end connection or nongasketed connection? Example: BS vs. BSG Elbow:

BS

Gustafson G-0 or Nongasketed Elbow

BSG

Gustafson G-3 or Gasketed Elbow

DUCT SR = single wall round, spiral duct

ELBOWS B = elbow
S = radius of 1.5 (standard)
w/o "S" radius = 1.0 radius (nonstandard)
F = fabricated (aka not stamped)
G = gasketed

REDUCERS R = reducer
C = concentric or center taper
F = female
G = gasketed
L = long

TAPS P = pressed
S = saddle
G = gasketed
V = 45°
B = boot-style
R = non-specific
C = concentric or center taper

TEES B = boot-style
T = tee
G = gasketed
C = concentric/center
P = pressed

TAKE-OFFS IL = initial leg
R = bell mouth type or *radiused*
G = gasketed

CROSSING TEES X = cross
C = center
P = pressed
G = gasketed
B = boot-style

LATERAL TEES T = tee
V = 45°
G = gasketed
45 = angle of take-off
X = take-off each side

Y-BRANCH Y = wye
V = 45°
G = gasketed

END CAPS E = end cap
S = fits inside duct
G = gasketed
P = fits outer duct
F = female
H = handle

DAMPERS D = damper
S = full blade
R = slotted damper blade
T = gasketed blade
G = gasketed
I = insulated

COUPLINGS MF = outer coupling
NP = inner coupling